

# revolution



Shown: RTP10  
10,000 lbs. capacity

## RTP10 Features:

- Overhead padded switch bar to avoid vehicle damage from being raised too high
- 3-stage front arm design enables you to position doors in front of column or behind to avoid door damage
- Top mounted pull design hydraulic cylinder.  
The piston rod is protected behind the carriage to prevent damage
- Overhead cable equalization
- Spring operated arm restraints, disengage at floor level
- Single point lock release
- Two full-stroke cylinders with overhead cable for equalization
- Large rubber-padded swivel truck adapters with extra height extensions are standard

Specifications	RTP10
Capacity	10,000 lbs.
Rise	77"
Overall Height	143-1/8"
Overall Width	131" (optional 137")
Drive Through Clearance	97" (optional 103")
Overhead Switch Height	136-1/4"
Front Reach (Min/Max)	23"/44-1/2"
Rear Reach (Min/Max)	38-7/8" / 58"
Min/Max Adapter Height	3-5/8"/10"
Width Inside Column	109-3/4" (optional 115-3/4")
Voltage/Amps	208/230, 20 amps
Motor/Phase	2 HP/2 HP/1Ø*
Ceiling Height Required	144"

\*Optional 3-phase available.

## Gold Certified

Revolution's RTP10 is ALI Certified. It takes a combination of the right design, engineering excellence and quality manufacturing to earn this certification. It is extra assurance for you that your lift meets the highest industry safety and performance standards. Look for the Gold label.

